



可逆式无段变速马达特性表 Reversible Speed Control Motor

马达型号 Motor Mode1 No.		出力 Force W	电压 Voltage V	周波数 Peripheral Wave No Hz	极数 Pole No	可变速度范围 Variable Speed Range		许容转矩 Turning Moment gcm		启动转矩 Start Turning Moment gcm	电流 Current A	启动电容 Start condenser	
圆柱出力轴 Cylindrical Output Shaft	小齿切出力轴 Pinion Cut Output Shaft					回转速 Revolving No.rpm	调数比 Ratio	设定回转速 Set Revolving No				容量 Capacity μF	耐电压 Resistance Voltage V
		1200rpm	90rpm										
2RK6RA-A	2RK6RGN-A	6	110	50	4	90~1400	1:15	460	250	330	0.28	3	250
			110	60		90~1700							
2RK6RA-C	2RK6RGN-C	6	220	50	4	90~1400	1:15	460	250	330	0.14	0.8	500
			220	60		90~1700							
3RK15RA-A	3RK15RGN-A	15	110	50	4	90~1400	1:15	880	300	550	0.45	5.0	250
			110	60		90~1700		660					
3RK15RA-C	3RK15RGN-C	15	220	50	4	90~1400	1:15	880	300	550	0.22	1.2	500
			220	60		90~1700		660					
4RK25RA-A	4RK25RGN-A	25	110	50	4	90~1400	1:15	1760	450	1200	0.60	7.0	250
			110	60		90~1700		1400					
4RK25RA-C	4RK25RGN-C	25	220	50	4	90~1400	1:15	1760	450	1200	0.30	1.8	500
			220	60		90~1700		1400					
5RK40RA-A	5RK40RGN-A	40	110	50	4	90~1400	1:15	2800	550	1900	0.9	10	250
			110	60		90~1700		1800					
5RK40RA-C	5RK40RGN/GU-C	40	220	50	4	90~1400	1:15	2800	550	1900	0.45	2.5	500
			220	60		90~1700		1800					
5RK60RA-A	5RK60RGN/GU-A	60	110	50	4	90~1400	1:15	5000	700	3000	1.1	14	250
			110	60		90~1700		3500					
5RK60RA-C	5RK60RGN/GU-C	60	220	50	4	90~1400	1:15	5000	700	3000	0.55	3.5	500
			220	60		90~1700		3500					
5RK90RA-A	5RK90RGN/GU-A	90	110	50	4	90~1400	1:15	6600	1100	4500	2.0	20	250
			110	60		90~1700		5300					
5RK90RA-C	5RK90RGN/GU-C	90	220	50	4	90~1400	1:15	6600	1100	4500	1.0	5.5	500
			220	60		90~1700		5300					
5RK120RA-A	5RK120RGN/GU-A	120	110	50	4	90~1400	1:15	8800	1500	6000	2.4	30	250
			110	60		90~1700		7000					
5RK120RA-C	5RK120RGN/GU-C	120	220	50	4	90~1400	1:15	8800	1500	6000	1.2	7	500
			220	60		90~1700		7000					
6RK140RA-A	6RK140RGN/GU-A	140	110	50	4	90~1400	1:15	10500	1750	7000	2.8	35	250
			110	60		90~1700		8200					
6RK140RA-C	6RK140RGN/GU-C	140	220	50	4	90~1400	1:15	10500	1750	7000	1.4	10	500
			220	60		90~1700		8200					
6RK180RA-A	6RK180RGN/GU-A	180	110	50	4	90~1400	1:15	13500	2500	9000	2.3	50	250
			110	60		90~1700		10500					
6RK180RA-C	6RK180RGN/GU-C	180	220	50	4	90~1400	1:15	13500	2500	9000	1.6	12	500
			220	60		90~1700		10500					

外型尺寸: External dimension

